

# MATERIAL SAFETY DATA SHEET

(Essentially similar to OSHA form 174, Sept. 1985 - ( For compliance with OSHA's Hazard Communication Standard, 29CFR 1910.1200)

## Storm Stain Enduradeck Fast Dry Deck & Fence Primer Linseed Alkyd Oil No. 23450

**SECTION PRODUCT IDENTITY:**

**MANUFACTURER'S NAME:**  
California Products Corporation  
**STREET ADDRESS:** 150 Dascomb Road  
**CITY / STATE:** Andover, MA  
**ZIP CODE:** 01810  
**MAIL ADDRESS:**  
150 Dascomb Road  
Andover, MA 01810

**DATE OF PREPARATION:** February, 2007  
**INFORMATION TELEPHONE NO.:**  
(978) 623-9980 Ext. 223  
**EMERGENCY TELEPHONE NO's.:**  
Weekdays: (978) 623-9980 Ext. 223  
(After hours, weekends & holidays)  
"CHEM-TEL"  
**Emergency Contact Number:** (800) 255-3924

**SECTION II - Hazardous Ingredients/Identity Information**

HAZARDOUS COMPONENT	COMMON NAME (S)	%	CAS. NO.	OSHA OR PEL	ACGIH TLV
*Ethylene glycol	(same)	<5.0	107-21-1	50 ppm	

**NOTE:** This product contains bentonite clays classified as "nuisance dusts". These products also contain more than 0.1% crystalline silica (CAS No. 14808-60-7) which has been classified by IARC as a Class I carcinogen. Normal application procedures pose no hazard since the silica is wet and encapsulated, but grinding or sanding dried films of this product may yield respirable silica dusts. Control exposures to less than 0.1 mg/m<sup>3</sup> using NIOSH-approved dust filter respirators.

**SECTION II - Physical/Chemical Characteristics (See reference Note (s) No. on Reverse)**

Boiling Points of Major Constituent: (Water) Min. Spirits	212½ F	Specific Gravity (H <sub>2</sub> O=1) WGT/GAL	11.2
Vapor Pressure (mm Hg) @ 68½C (Water)	17	Melting Point Water (Ice) Above	32½ F
Vapor Density (AIR=1) Heavier Lighter	X	Evaporation Rate (Butyl Acetate=1)	Slower
Solubility in Water	Total	Appearance and Odor	Viscous liquid; slight ammoniacal odor
			Maximum VOC's 250 g/l

**SECTION IV - Fire and Explosion Hazard Data: Non-Flammable**

Flash Point: Non-Combustible	Flammable Limits: LEL: N/A UEL: N/A	DOT Hazard Class: Not regulated	Marking: "Keep from Freezing"
------------------------------	--	------------------------------------	-------------------------------

**SECTION V - Reactivity Data**

**HAZARDOUS POLYMERIZATION:** Will not occur.

**STABILITY:** Stable

**INCOMPATIBILITY:** Avoid contact with: Strong oxidating agents (i.e. nitric acid, permanganates, etc)

**HAZARDOUS DECOMPOSITION PRODUCTS:** Some carbon monoxide generated during burning.

**SECTION VI - Health Hazard Data, Toxicity Data: ethylene glycol Oral LD<sub>50</sub> (rat)=8.54 g/kg**

**Route (s) of Entry:** N/A **Carcinogenicity?**

**Health Hazards (Acute and Chronic):**

**EFFECTS OF OVEREXPOSURE:** Inhalation: Vapors or spray mists may be slightly irritating to eye, nose, throat and mucous membranes of respiratory tract, producing symptoms of headache and nausea in poorly ventilated areas. Skin contact: Prolonged or repeated contact with coating may cause slight skin irritation. Eye contact: Direct contact: Inconsequential eye irritation.

**EMERGENCY AND FIRST AID PROCEDURES:** Eye and skin contact: Immediately flush eyes with plenty of water for at least 15 minutes and consult physician; wash skin thoroughly with soap and water; if drenched, remove and wash clothing before reuse. Ingestion: If victim is conscious, give 2 glasses of water. Call a physician.

\*Note: This product contains this toxic chemical subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

**SUPPLEMENTAL INFORMATION**

To comply with New Jersey DOH Right-To-Know labelling law (N.J.A.C. 8:59 - 5.1 & 5.2)

CAS NO.	CHEMICAL INGREDIENTS
55406-53-6	3-Iodo-2-propynyl carbamate
1732-18-5	Water
107-21-1	Ethylene Glycol
14808-60-7	Crystalline Silica
Not Available	Latex Resin Solids
(+ ) Contents Partially Unknown	

HMIS HAZARD RATING			
Health 1	Flammability 0	Physical Hazard 0	Personal Protection A
<b>HAZARD INDEX</b>			
0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe			
<b>PERSONAL PROTECTION CODE</b>			
A- Safety Glasses			

Warning! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD (5323) or log on to: [www.epa.gov/lead](http://www.epa.gov/lead).

