

**Hardwood Oil Deck Finish - Toned
2004X****Product Description:**

Storm Stain Hardwood Oil Deck Finish provides maximum protection to exterior wood decks and surfaces exposed to water, ultraviolet rays and general atmospheric contamination including acid rain. This durable resin seals, waterproofs and protects exterior wood decks subject to the rigors of drastic weather and temperature changes. This Hardwood Oil Deck Finish restricts cracking, peeling and blistering and can be used on new wood, previously stained wood and new pressure treated wood with proper preparation. One coat should be applied over new or previously stained or finished decks that have aged and have been properly prepared. Storm Stain Hardwood Oil Deck Finish is formulated for maximum abrasion on wear areas. Excellent for use on dense hardwoods such as mahogany, teack, fir, etc.

Recommended Use:

Sundecks, Wood Walkways, Railings and Posts, Open Porches, Fencing, Wood Screening, Benches, Patios, Trellis, Garden Enclosures, Outdoor Furniture, Wood Enclosures

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

STORM STAIN ENDURAKECK® HARDWOOD OIL DECK FINISH is best applied by natural bristle brush but can be rolled or sprayed. Clean brushes and equipment with mineral spirits and remove spatter immediately after completion of job.

Architectural Specifications:

- UNFINISHED WOOD DECKS, RAILS, POSTS, FENCES, PATIOS, SCREENING, AND OUTDOOR FURNITURE
One coat Storm Stain Hardwood Oil Deck Finish 2004X
- PREVIOUSLY STAINED SURFACES (after proper preparation)
One coat Storm Stain Hardwood Oil Deck Finish 2004X
- PRESSURE TREATED WOOD
One coat Storm Stain Hardwood Oil Deck Finish 2004X

Precautions:

Remove all mildew before application. Do not use over previously sealed, stained, painted or varnished surfaces. Do not use on clapboards, shingles, or shakes. Chemicals used for pressure treating wood may slightly alter decking stain colors but will not harm the stain. Air and surface temperatures must be 50° F or higher during application and drying times. Low temperatures, high humidity or thick application will greatly retard drying time.

New pressure treated wood must be thoroughly scrubbed with a solution of tri-sodium phosphate and water, rinsed clean and allowed to dry completely prior to finishing. A green cast may show through for a few months as the preservatives leach from the wood. Do not use inter-changeably on the same surface as Storm stain Semi-Transparent Stains. Sheen variations will show.

Appearance varies with the different varieties of wood. Samples should be tested on the actual wood being used before large areas of wood are finished. This product is designed for one coat application only.

CAUTION: All floor coatings are more slippery when the surface becomes wet or contaminated with debris. To help reduce the potential for slipping, coated areas must be kept dry and properly cleaned of dirt, oils, food and beverage residue, water, snow, ice and any other contaminants.

Safety Information:

CAUTION! COMBUSTIBLE! Use only with adequate ventilation. Keep out of reach of children. Do not take internally. Close container after each use.

Product Specifications:

Type:	Alkyd
Exposure:	Exterior
Specular Gloss:	12 @ 60° ± 5
Volume Solids:	26.5% ± 2
Solids by Weight:	32.9% ± 2
Vehicle:	96.7% ± 2
Pigment:	3.3% ± 2
Dry Film Thickness:	1.1 mils
Viscosity @ 77 °F:	50 KU ± 5
Maximum VOC:	575g/liter
Flash Pt °F:	103
Thinner:	Mineral Spirits
Clean Up:	Mineral Spirits

Available Colors and Bases:

4 Stock

Available Package Sizes:

Gallon

(Weight Per Gallon: 7.1 lbs. ± .5 lb)

Drying Times:

To Touch:	4 hrs.
To Handle:	12 hrs.
To Recoat:	0 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth:	375-425 s.f./gal.
Porous:	300-350 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush -
Synthetic, Nylon or Polyester

Roller -
3/8" Nap Synthetic Fiber

Airless Spray -
.017 to .019 Tip