



Enduradeck® Alkyd Linseed Oil Deck Stain - Semi-Opaque 240XX

Product Description:

Storm Stain Decking Stain is an alkyd linseed oil wear resistant semi-transparent stain designed for use on decks and other exposed flat areas subjected to the rigors of drastic weather and temperature change, abrasion and acid rain or snow. These decking stains provide maximum protection against water, ultraviolet rays and general atmospheric contamination. Storm Stain Decking Stain resists cracking, peeling and blistering, and can be used on new wood, previously stained wood and properly prepared pressure treated wood.

Recommended Use:

Sundecks, Wood Walkways, Railings and Posts, Open Porches, Fencing, Wood Screening, Benches, Patios, Trellis, Garden Enclosures

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Architectural Specifications:

- UNFINISHED WOOD DECKS, RAILS, POSTS, FENCES, PATIOS, SCREENING, AND OUTDOOR FURNITURE
2 coats Storm Stain Semi-Transparent Decking Stain 240XX
- PREVIOUSLY STAINED SURFACES
1 or 2 coats Storm Stain Semi-Transparent Decking Stain 240XX
- PRESSURE TREATED WOOD
1 or 2 coats Storm Stain Semi-Transparent Decking Stain 240XX

NOTES:

1. New pressure treated wood must be thoroughly scrubbed with a solution of tri-sodium phosphate and water, rinsed clean and allowed to dry completely prior to staining. Light colors may have a green cast for a few months as the preservatives leach from the wood.
2. Do not use inter-changeably on the same surface as Storm stain Semi-Transparent Stains. Sheen variations will show.
3. Decking Stain colors vary with the different varieties of wood. Samples should be tested on the actual wood being used before large areas of wood are stained.

Precautions:

Remove all mildew before application. Do not use over previously sealed, stained, painted or varnished surfaces. Do not use on clapboards, shingles, or shakes. Chemicals used for pressure treating wood may slightly alter decking stain colors but will not harm the stain. Air and surface temperatures must be 50° F or higher during application and drying times.

CAUTION: All floor coatings are more slippery when the surface becomes wet or contaminated with debris. To help reduce the potential for slipping, coated areas must be kept dry and properly cleaned of dirt, oils, food and beverage residue, water, snow, ice and any other contaminants.

Safety Information:

CAUTION! COMBUSTIBLE! Use only with adequate ventilation. Keep out of reach of children. Do not take internally. Close container after each use.

Product Specifications:

Type: Alkyd Linseed Oil
Exposure: Exterior
Specular Gloss: 12@ 60° ± 3
Volume Solids: 32.2 % ±2
Solids by Weight: 41.1 % ±2
Vehicle: 95 % ±2
Pigment: 5 % ±2
Dry Film Thickness: 1.4 mils
Viscosity @ 77 °F: KU ±5
Maximum VOC: 550 g/liter
Flash Pt °F: 103
Thinner: Mineral Spirits
Clean Up: Mineral Spirits

Available Colors and Bases:

6 Stock Cleartone

Available Package Sizes:

Gallon

(Weight Per Gallon: 7.5 lbs. ± .5 lb)

Drying Times:

To Touch: 3 hrs.
To Handle: 3 hrs.
To Recoat: 16 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 350-400 s.f./gal.
Porous: 200-250 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush -
Natural Bristle

Roller -
3/8" Nap Synthetic

Airless Spray -
.017-.019 tip