



**Enduradeck Semi-Opaque Deck, Fence and Siding Stain
240XX**

<p>Product Description:</p>	<p>Product Specifications:</p>
<p>Enduradeck Semi-Opaque Deck, Fence and Siding Stain is designed for use on decks and other exterior areas including vertical siding, fences and railings. This semi-opaque stain resists cracking, peeling blistering and can be used on new wood as well as previously stained and properly prepared pressure treated wood. This semi opaque stain is self priming and provides maximum protection against water, ultra-violet rays and general atmospheric contamination.</p>	<p>Type: Alkyd Linseed Oil Exposure: Exterior Specular Gloss: 12 @ 60° ± 3 Volume Solids: 32.2% ± 2 Solids by Weight: 41.1% ± 2 Vehicle: 95% ± 2 Pigment: 5% ± 2 Dry Film Thickness: 1.4 mils Viscosity @ 77 °F: KU ± 5 Maximum VOC: 550 g/liter Flash Pt °F: 103 Thinner: Mineral Spirits Clean Up: Mineral Spirits</p>
<p>Recommended Use:</p> <p>Sundecks, Wood Walkways, Railings and Posts, Open Porches, Fencing, Wood Screening, Benches, Patios, Trellis, Garden Enclosures and Siding</p>	<p>Available Colors and Bases:</p> <p>6 Stock Cleartone</p>
<p>Application:</p> <p>WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.</p>	<p>Available Package Sizes:</p> <p>Gallon</p> <p>(Weight Per Gallon: 7.5 lbs. ± .5 lb)</p>
<p>Architectural Specifications:</p> <ul style="list-style-type: none"> ▪ UNFINISHED WOOD DECKS, RAILS, POSTS, FENCES, PATIOS, SCREENING, SIDING, AND OUTDOOR FURNITURE 2 coats Storm Stain Semi-Opaque Decking Stain 240XX ▪ PREVIOUSLY STAINED SURFACES 1 or 2 coats Storm Stain Semi-Opaque Decking Stain 240XX ▪ PRESSURE TREATED WOOD 1 or 2 coats Storm Stain Semi-Opaque Decking Stain 240XX <p>NOTES:</p> <ol style="list-style-type: none"> 1. New pressure treated wood must be thoroughly scrubbed with a solution of tri-sodium phosphate and water, rinsed clean and allowed to dry completely prior to staining. Light colors may have a green cast for a few months as the preservatives leach from the wood. 2. Do not use inter-changeably on the same surface as Storm stain Semi-Transparent Stains. Sheen variations will show. 3. Stain colors vary with the different varieties of wood. Samples should be tested on the actual wood being used before large areas of wood are stained. 	<p>Drying Times:</p> <p>To Touch: 3 hrs. To Handle: 3 hrs. To Recoat: 16 hrs.</p> <p>(@ 70-77 °F, 50% R.H.)</p>
<p>Precautions:</p> <p>Remove all mildew before application. Do not use over previously sealed, painted or varnished surfaces. Chemicals used for pressure treating wood may slightly alter decking stain colors but will not harm the stain. Air and surface temperatures must be 50° F or higher during application and drying times.</p> <p>CAUTION: All floor coatings are more slippery when the surface becomes wet or contaminated with debris. To help reduce the potential for slipping, coated areas must be kept dry and properly cleaned of dirt, oils, food and beverage residue, water, snow, ice and any other contaminants.</p>	<p>Surface Spread Rate:</p> <p>Smooth: 350-400 s.f./gal. Porous: 200-250 s.f./gal.</p> <p>(Spray Application is 50% of above)</p>
<p>Safety Information:</p> <p>CAUTION! COMBUSTIBLE! Use only with adequate ventilation. Keep out of reach of children. Do not take internally. Close container after each use.</p>	<p>Tools and Equipment:</p> <p>Brush - Natural Bristle</p> <p>Roller - 3/8" Nap Synthetic</p> <p>Airless Spray - .017-.019 tip</p>